Article number 46115

Viessmann Modelltechnik GmbH





Date printed 17.05.2017, Revision 17.05.2017 Version 01 Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Vollmer Supranol 2000 Article number: 46115

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Plastic - adhesive

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Viessmann Modelltechnik GmbH

Bahnhofstraße 2a

35116 Hatzfeld-Reddighausen / GERMANY

Phone +49(0)6452 93400 Fax +49(0)6452 934019

Homepage www.viessmann-modell.de E-mail info@viessmann-modell.com

Address enquiries to

Technical informationinfo@viessmann-modell.comSafety Data Sheetsdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +49 (0) 6131-19240 (24h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flam. Liq. 3: H226 Flammable liquid and vapour. STOT SE 3: H336 May cause drowsiness or dizziness.

2.2 Label elements

Signal word

Contains:

Hazard pictograms



WARNING n-Butyl acetate

Hazard statements H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area.

P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection.

P312 Call a POISON CENTER / doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/national regulation.

Special labelling EUH066 Repeated exposure may cause skin dryness or cracking.



Volimer Supranor 2000

Article number 46115

Viessmann Modelltechnik GmbH

35116 Hatzfeld-Reddighausen



Date printed 17.05.2017, Revision 17.05.2017 Version 01 Page 2 / 10

2.3 Other hazards

Physico-chemical hazards Evolution of flammable mixtures possible in air when heated above flash point and/or during

spraying or misting.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
70 - 90	n-Butyl acetate
	CAS: 123-86-4, EINECS/ELINCS: 204-658-1, EU-INDEX: 607-025-00-1, Reg-No.: 01-2119485493-29-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - STOT SE 3: H336

Comment on component parts Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Remove person to fresh air and keep comfortable for breathing.

In the event of symptoms seek medical treatment.

Skin contact When in contact with the skin, clean with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Consult a doctor immediately.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects Vertigo Drowsiness Headache

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide.

Extinguishing media that must not

be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

Article number 46115

Viessmann Modelltechnik GmbH

35116 Hatzfeld-Reddighausen



Date printed 17.05.2017, Revision 17.05.2017

Version 01

Page 3 / 10

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Do not inhale explosion and/or combustion gases.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from all sources of ignition.

Ensure adequate ventilation.

High risk of slipping due to leakage/spillage of product.

Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.

Keep away from all sources of ignition - Refrain from smoking.

Vapours can form an explosive mixture with air.

Ignitable mixtures can be formed in the empty container.

Use explosion-proofed equipment/fittings and non-sparkling tools.

Take off contaminated clothing and wash before reuse.

Do not eat, drink or smoke when using this product.

After worktime and before work breaks the affected skin areas must be thoroughly cleaned.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Do not store together with food and animal food/diet.

Keep container tightly closed.

Keep container in a well-ventilated place. Protect from heat/overheating and from sun.

7.3 Specific end use(s)

See product use, SECTION 1.2

Article number 46115

Viessmann Modelltechnik GmbH

35116 Hatzfeld-Reddighausen



Date printed 17.05.2017, Revision 17.05.2017 Version 01 Page 4 / 10

SECTION 8: Exposure controls / personal protection

Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance

n-Butyl acetate

CAS: 123-86-4, EINECS/ELINCS: 204-658-1, EU-INDEX: 607-025-00-1, Reg-No.: 01-2119485493-29-XXXX

Long-term exposure: 150 ppm, 724 mg/m³

Short-term exposure (15-minute): 200 ppm, 966 mg/m³

DNEL

Substance

n-Butyl acetate, CAS: 123-86-4

Industrial, inhalative, Long-term - local effects: 480 mg/m³

Industrial, inhalative, Long-term - systemic effects: 480 mg/m³.

Industrial, inhalative, Acute - systemic effects: 960 mg/m3.

Industrial, inhalative, Acute - local effects: 960 mg/m³

general population, inhalative, Long-term - local effects: 102,34 mg/m3.

general population, inhalative, Long-term - systemic effects: 102,34 mg/m³

general population, inhalative, Acute - local effects: 859,7 mg/m³

general population, inhalative, Acute - systemic effects: 859,7 mg/m³.

PNEC

Substance

n-Butyl acetate, CAS: 123-86-4

soil, 0,0903 mg/kg.

sediment (seaater), 0,0981 mg/kg

sediment (freshwater), 0,981 mg/kg

sewage treatment plants (STP), 35,6 mg/l.

seawater, 0,018 mg/l

freshwater, 0,18 mg/l

8.2 **Exposure controls**

Additional advice on system design Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection safety glasses (EN 166:2001)

Hand protection 0,4 mm Butyl rubber, >480 min (EN 374-1/-2/-3).

The details concerned are recommendations. Please contact the glove supplier for further

information.

Protective clothing. Skin protection

Other Avoid contact with eyes and skin.

Do not inhale vapours.

Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Respiratory protection Respiratory protection mask in the event of high concentrations.

Short term: filter apparatus, combination filter A-P2. (DIN EN 14387)

Thermal hazards

Delimitation and monitoring of the

environmental exposition

Protect the environment by applying appropriate control measures to prevent or limit

emissions.

Safety Data Sheet 1907/2006/EC - REACH (GB)

Vollmer Supranol 2000

Article number 46115

Viessmann Modelltechnik GmbH

35116 Hatzfeld-Reddighausen



Date printed 17.05.2017, Revision 17.05.2017 Version 01 Page 5 / 10

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form liquid

Color colourless

Odor characteristic

Odour threshold not required

pH-value not applicable

pH-value [1%] not applicable

Boiling point [°C] 126
Flash point [°C] 27

Flammability (solid, gas) [°C] not determined
Lower explosion limit 1,2 Vol.-%
Upper explosion limit 7,5 Vol.-%
Oxidising properties no

Vapour pressure/gas pressure [kPa] ~ 1,5 (20°C)

Density [g/ml] ~ 0,9

Bulk density [kg/m³] not applicable

Solubility in water partially soluble

Partition coefficient [n-octanol/water] No information available.

Viscosity not applicable

Relative vapour density determined

in air

No information available.

Evaporation speed No information available.

Melting point [°C] No information available.

Autoignition temperature [°C] > 300

Decomposition temperature [°C] No information available.

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Heating

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.



Date printed 17.05.2017, Revision 17.05.2017 Version 01 Page 6 / 10

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product ATE-mix, inhalativ (vapour), > 20 mg/l 4h. ATE-mix, dermal, > 2000 mg/kg. ATE-mix, oral, > 2000 mg/kg.

Substance

n-Butyl acetate, CAS: 123-86-4

LD50, dermal, Rabbit: >14112 mg/kg (OECD 402)

LD50, oral, Rat: 10760 mg/kg (OECD 423).

LC50, inhalative, Rat: 23.4 mg/l (4h) (OECD 403)

Serious eye damage/irritation Does not contain a relevant substance that meets the classification criteria.

Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available.

Skin corrosion/irritation Does not contain a relevant substance that meets the classification criteria.

Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available.

Respiratory or skin sensitisation Does not contain a relevant substance that meets the classification criteria.

Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available.

Specific target organ toxicity —

single exposure

Vapours may cause drowsiness and dizziness.

Based on the available information, the classification criteria are fulfilled.

Toxicological data of complete product are not available.

Calculation method

Specific target organ toxicity —

repeated exposure

Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available.

Mutagenicity Does not contain a relevant substance that meets the classification criteria.

Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available.

Does not contain a relevant substance that meets the classification criteria. Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available.

Carcinogenicity Does not contain a relevant substance that meets the classification criteria.

Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available.

Aspiration hazard Does not contain a relevant substance that meets the classification criteria.

Based on the available information, the classification criteria are not fulfilled.

General remarks

none

SECTION 12: Ecological information

12.1 Toxicity

Substance	
n-Butyl acetate, CAS: 123-86-4	
LC50, (96h), Pimephales promelas: 18 mg/l (OECD 203).	
EC50, (72h), Desmodesmus subspicatus: 647.7 mg/l.	
EC50, (48h), Daphnia magna: 44 mg/l.	
IC50, Bacteria: 356 mg/l (40 h).	
NOEC, Desmodesmus subspicatus: 200 mg/l.	

Safety Data Sheet 1907/2006/EC - REACH (GB) Vollmer Supranol 2000 Article number 46115 Viessmann Modelltechnik GmbH



Date printed 17.05.2017, Revision 17.05.2017

Version 01

Page 7 / 10

12.2 Persistence and degradability

35116 Hatzfeld-Reddighausen

Behaviour in environment

not determined

compartments

not determined

Behaviour in sewage plant Biological degradability

not determined

12.3 Bioaccumulative potential

Accumulation in organisms is not expected.

12.4 Mobility in soil

Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Coordinate disposal with the authorities if necessary.

Waste no. (recommended) 080409*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110*

SECTION 14: Transport information

14.1 UN number

Transport by land according to

ADR/RID

1123

Inland navigation (ADN) 1123

Marine transport in accordance with 11

IMDG

Air transport in accordance with IATA 1123

Safety Data Sheet 1907/2006/EC - REACH (GB)

Vollmer Supranol 2000

Article number 46115

Viessmann Modelltechnik GmbH

35116 Hatzfeld-Reddighausen



Date printed 17.05.2017, Revision 17.05.2017 Version 01 Page 8 / 10

14.2 UN proper shipping name

Transport by land according to

ADR/RID

- Classification Code

- Label

F1

Butyl acetates, solution

Butyl acetates, solution

Butyl acetates, solution

- ADR LQ

- ADR 1.1.3.6 (8.6)

Transport category (tunnel restriction code) 3 (D/E)

Inland navigation (ADN)

- Classification Code

- Label



Marine transport in accordance with

IMDG

F-E, S-D

- EMS - Label

- IMDG LQ

Air transport in accordance with IATA Butyl acetates, solution

- Label



14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

3

3

Inland navigation (ADN)

Marine transport in accordance with 3

IMDG

Air transport in accordance with IATA 3

14.4 Packing group

Transport by land according to

ADR/RID

Ш

Inland navigation (ADN)

Ш

Marine transport in accordance with

IMDG

Air transport in accordance with IATA III

Safety Data Sheet 1907/2006/EC - REACH (GB)
Vollmer Supranol 2000
Article number 46115

Article number 46115
Viessmann Modelltechnik GmbH
35116 Hatzfeld-Reddighausen



Date printed 17.05.2017, Revision 17.05.2017 Version 01 Page 9 / 10

14.5 Environmental hazards

Transport by land according to

ADR/RID

no

Inland navigation (ADN)

Marine transport in accordance with new

IMDG

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008;

75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS DOT-Classification, ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2017).

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

CHIP 3/ CHIP 4

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers. Observe

employment restrictions for young people.

- VOC (2010/75/CE) 85 %

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 03)

H336 May cause drowsiness or dizziness. H226 Flammable liquid and vapour. Safety Data Sheet 1907/2006/EC - REACH (GB) **Vollmer Supranol 2000** Article number 46115 Viessmann Modelltechnik GmbH 35116 Hatzfeld-Reddighausen



Date printed 17.05.2017, Revision 17.05.2017 Version 01 Page 10 / 10

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level DNEL = Derived No Effect Level EC50 = Median effective concentration ECB = European Chemicals Bureau

EEC = European Economic Community EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods IUCLID = International Uniform ChemicaL Information Database

LC50 = Lethal concentration, 50% LD50 = Median lethal dose

LC0 = lethal concentration, 0% LOAEL = lowest-observed-adverse-effect level

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value - time-weighted average TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure Flam. Liq. 3: H226 Flammable liquid and vapour. (On basis of test data)

STOT SE 3: H336 May cause drowsiness or dizziness. (Calculation method)

Modified position none



Copyright: Chemiebüro®

